

# Commercial Illumination




LED Step Light Series






## Specifications

Item No.	WR-0001-LD-100	WR-0001-LD-103	WR-0002-LD-200
Light Source	9x1W High Power LEDs	9x1W High Power LEDs	9x1W High Power LEDs
Beam Angle	35°	79.5°	25.5°
Color	White	White	White
Operating Current	15mA	350mA	15mA
Power Consumption			
Lighting Fixture	Die casting aluminum	Die casting aluminum	Die casting aluminum
Glass	Frosted glass	Frosted glass	Frosted glass
Electrical Wire	2468 24AWGX2C 15m with DC plug	2468 24AWGX2C 15m with DC plug	2468 24AWGX2C 15m with DC plug
Operating Temperature	-30°C ~ +50°C	-30°C ~ +50°C	-30°C ~ +50°C

## Dimensional Diagrams









## Candle Power Distribution





WR-0003-LD-300	WR-0004-LD-400	WR-0005-LD-500
9x1W High Power LEDs	12x1W High Power LEDs	12x1W High Power LEDs
41°	25°	36.5°
White	White	White
15mA	15mA	15mA
Die casting aluminum	Die casting aluminum	Die casting aluminum
Frosted glass	Frosted glass	Frosted glass
2468 24AWGX2C 15m with DC plug	2468 24AWGX2C 15m with DC plug	2468 24AWGX2C 15m with DC plug
-30°C ~ +50°C	-30°C ~ +50°C	-30°C ~ +50°C



# Commercial Illumination




LED Step Light Series






## Specifications

Item No.	WR-0005-LD-503	WR-0006-LD-600	WR-0006-LD-603
Light Source	3x1W High Power LEDs	12x1W High Power LEDs	3x1W High Power LEDs
Beam Angle	87°	35°	74°
Color	White	White	White
Operating Current	350mA	15mA	350mA
Power Consumption			
Lighting Fixture	Die casting aluminum	Die casting aluminum	Die casting aluminum
Glass	Frosted glass	Frosted glass	Frosted glass
Electrical Wire	2468 24AWGX2C 15m with DC plug	2468 24AWGX2C 15m with DC plug	2468 24AWGX2C 15m with DC plug
Operating Temperature	-30°C ~ +50°C	-30°C ~ +50°C	-30°C ~ +50°C

## Dimensional Diagrams



## Candle Power Distribution





WR-0007-LD-700	LBM-PC-001	LBM-PC-002
12x1W High Power LEDs	24W+12Y 3528 SMD LEDs	12x1W High Power LEDs
32°	25°	36.5°
White	White	White
15mA	15mA	15mA
	3W	
Die casting aluminum	Die casting aluminum	Die casting aluminum
Frosted glass	Frosted glass	Frosted glass
2468 24AWGX2C 15m with DC plug	2468 24AWGX2C 15m with DC plug	2468 24AWGX2C 15m with DC plug
-30°C ~ +50°C	-30°C ~ +50°C	-30°C ~ +50°C

