

Industrial Illumination




LED Bay Series






Specifications

| Item No. | 91304 | 91314 | 91324 |
|-----------------------|---------------------|---------------------|---------------------|
| Light Source | High Power LED | High Power LED | High Power LED |
| Beam Angle | 70° | 70° | 70° |
| Input Voltage | 100-240V AC 50/60Hz | 100-240V AC 50/60Hz | 100-240V AC 50/60Hz |
| Power Consumption | 45W | 60W | 85W |
| Color Temperature | WW / NW / CW | WW / NW / CW | WW / NW / CW |
| Luminous Flux | 1870 Lm | 2370 Lm | 3270 Lm |
| Operating Temperature | -30°C ~ +40°C | -30°C ~ +40°C | -30°C ~ +40°C |

Dimensional Diagrams






Candle Power Distribution





| 90604 | 90604-1 |
|------------------|-----------------------|
| 80x1W White LEDs | 80x1W High Power LEDs |
| 86° | 73° |
| 100-240V AC | 100-240V AC 50/60Hz |
| 96W | 91.4W |
| 5000K(±500K) | 5000K(±500K) |
| 5420 Lm | 4260 Lm |
| -30°C ~ +40°C | -30°C ~ +40°C |
| P.F: >0.95 | P.F: >0.95 |



Industrial Illumination

LED Bay Series

Pendant Lowbay
Triac Dimmable





Surface Lowbay
Triac Dimmable




Specifications

| Item No. | 90494/90614 | 90504/90514 | 90524/90624 |
|------------------------------|--|--|--|
| Light Source | High Power White LEDs | High Power White LEDs | High Power White LEDs |
| Beam Angle | 77° | 77° | 77° |
| Input Voltage | 90494: 220-240V AC 50Hz 90614: 100-120V AC 60Hz | 90504: 220-240V AC 50Hz 90514: 100-120V AC 60Hz | 90524: 220-240V AC 50Hz 90624: 100-120V AC 60Hz |
| Power Consumption | 12W | 14W | 12W |
| Color Temperature | WW / NW / CW | WW / NW / CW | WW / NW / CW |
| Luminous Flux | 770 Lm | 720 Lm | 770 Lm |
| Operating Temperature | -30°C ~ +40°C | -30°C ~ +40°C | -30°C ~ +40°C |
| P.F | >0.90 | >0.90 | >0.90 |

Dimensional Diagrams



Candle Power Distribution



Surface Lowbay
Triac Dimmable



Recessed Ceiling Lowbay
Triac Dimmable



| 90534/90544 | 90554/90634 | 90564/90574 |
|-------------------------|-------------------------|-------------------------|
| High Power White LEDs | High Power White LEDs | High Power White LEDs |
| 77° | 77° | 77° |
| 90534: 220-240V AC 50Hz | 90554: 220-240V AC 50Hz | 90564: 220-240V AC 50Hz |
| 90544: 100-120V AC 60Hz | 90634: 100-120V AC 60Hz | 90574: 100-120V AC 60Hz |
| 14W | 12W | 14W |
| WW / NW / CW | WW / NW / CW | WW / NW / CW |
| 720 Lm | 770 Lm | 720 Lm |
| -30°C ~ +40°C | -30°C ~ +40°C | -30°C ~ +40°C |
| >0.90 | >0.90 | >0.90 |

