

Industrial Illumination




LED Tunnel Series






Specifications

Item No.	SD-180-RY	SD-90-RY	SD-72-RY
Light Source	High Power LEDs	High Power LEDs	High Power LEDs
Beam Angle	120° x 90°	120° x 90°	120° x 90°
Color Temperature	WW / NW / CW	WW / NW / CW	WW / NW / CW
Luminous Flux	14350 Lm	7654 Lm	6081 Lm
Input Voltage	100~240V AC 50/60Hz	100~240V AC 50/60Hz	100~240V AC 50/60Hz
Power Consumption	200W	105W	86W
Operating Temperature	-30°C ~ +50°C	-30°C ~ +50°C	-30°C ~ +50°C
IP Rate	IP65	IP65	IP65

Dimensional Diagrams



Candle Power Distribution





SD-60-RY	SD-45-RY	NEOJ0075-000
High Power LEDs	High Power LEDs	High Power LEDs
120° x 90°	120° x 90°	82°
WW / NW / CW	WW / NW / CW	WW / NW / CW
5770 Lm	3656 Lm	3092 Lm
100~240V AC 50/60Hz	100~240V AC 50/60Hz	100-240V
73W	51W	79.5W
-30°C ~ +50°C	-30°C ~ +50°C	-30°C ~ +50°C
IP65	IP65	IP65

